

# A multi-party protocol for constructing the public parameters of the Pinocchio zk-SNARK

Sean Bowe, Ariel Gabizon, Matthew Green

October 29, 2016

## Abstract

Recent efficient constructions of zero-knowledge Succinct Non-interactive Arguments of Knowledge (zk-SNARKs), require a setup phase in which a common-reference string (CRS) with a certain structure is generated. This CRS is sometimes referred to as the *public parameters of the system*, and is used for constructing and verifying proofs. A drawback of these constructions is that whomever runs the setup phase subsequently possesses trapdoor information enabling them to produce fraudulent pseudoproofs.

Ben-Sasson, Chiesa, Green, Tromer and Virza [BCG<sup>+</sup>15] presented a generic method for computing this CRS in a multi-party protocol, with the property that only if all players collude together they can reconstruct the trapdoor, or, more generally, deduce any other useful information beyond the resultant CRS. Based on [BCG<sup>+</sup>15], we devise an arguably simpler method for generating the CRS of the Pinocchio zk-SNARK [PHGR16] with a similar security guarantee: Namely, given that the CRS generated by the protocol is later used to verify proofs; a party controlling all but one of the players will not be able to construct fraudulent proofs except with negligible probability. This method has been used in practice to generate the required CRS for the Zcash cryptocurrency blockchain.

**Organization of paper** Section 1 introduces some terminology and auxiliary methods that will be used in the protocol. Section 2 describes the protocol in detail. Section 3 describes the security proof of the protocol.

## 1 Definitions, notation and auxiliary methods

**Terminology:** We always assume we are working with a field  $\mathbb{F}_r$  for prime  $r$  chosen according to a desired security parameter (more details on this in Section 3). We assume together with  $\mathbb{F}_r$  we have generated groups  $\mathbb{G}_1, \mathbb{G}_2, \mathbb{G}_t$ , all cyclic of order  $r$ ; where we write  $\mathbb{G}_1$  and  $\mathbb{G}_2$  in additive notation and  $\mathbb{G}_t$  in multiplicative notation. Furthermore, we have access to generators  $g_1 \in \mathbb{G}_1, g_2 \in \mathbb{G}_2$ , and an efficiently computable pairing  $e : \mathbb{G}_1 \times \mathbb{G}_2 \rightarrow \mathbb{G}_t$ , i.e., a non-trivial map such that for any  $a, b \in \mathbb{F}_r$

$$e(a \cdot g_1, b \cdot g_2) = g_t^{a \cdot b},$$

for a fixed generator  $g_T \in \mathbb{G}_t$ . We use the notations  $g := (g_1, g_2)$  and  $G^* := \mathbb{G}_1 \setminus \{0\} \times \mathbb{G}_2 \setminus \{0\}$ .

We think of the field size  $r$  as a parameter against which we measure efficiency. In particular, we say a circuit  $A$  is *efficient* if its size is polynomial in  $\log r$ . More precisely, when we refer in the security analysis to an efficient adversary or efficient algorithm, we mean it is a (non-uniform)

sequence of circuits indexed by  $r$ , of size  $\text{poly log } r$ . When we say “with probability  $p$ ”, we mean “with probability at least  $p$ ”.

We assume we have at our disposal a function COMMIT taking as input strings of arbitrary length; that, intuitively speaking, behaves like a commitment scheme. That is, it is infeasible to deduce COMMIT’s input from seeing its output, and it is infeasible to find two inputs that COMMIT maps to the same output. In our implementation we use the BLAKE-2 hash function as COMMIT. For the actual security proof, we need to assume that COMMIT’s outputs are chosen by a random oracle.

**Symmetric definitions** In the following sections we introduce several methods that receive as parameters elements of both  $\mathbb{G}_1$  and  $\mathbb{G}_2$ . We assume implicitly that whenever such a definition is made, we also have the symmetric definition where the roles are reversed between what parameters come from  $\mathbb{G}_1$  and  $\mathbb{G}_2$ . For example, if we define a method receiving as input a vector of  $\mathbb{G}_1$  elements and a pair of  $\mathbb{G}_2$  elements. We assume thereafter that we also have the symmetric method receiving as input a vector of  $\mathbb{G}_2$  elements and a pair of  $\mathbb{G}_1$  elements.

## 1.1 Comparing ratios of pairs using pairings

**Definition 1.1.** *Given  $s \in \mathbb{F}_r^*$ , an  $s$ -pair is a pair  $(p, q)$  such that  $p, q \in \mathbb{G}_1 \setminus \{0\}$ , or  $p, q \in \mathbb{G}_2 \setminus \{0\}$ ; and  $s \cdot p = q$ . When not clear from the context whether  $p, q$  are in  $\mathbb{G}_1$  or  $\mathbb{G}_2$ , we use the terms  $\mathbb{G}_1$ - $s$ -pair and  $\mathbb{G}_2$ - $s$ -pair.*

A recurring theme in the protocol will be to check that two pairs of elements in  $\mathbb{G}_1$  and  $\mathbb{G}_2$  respectively, “have the same ratio”, i.e., are  $s$ -pairs for the same  $s \in \mathbb{F}_r^*$ .

SameRatio $((p, q), (f, H))$ :

1. If one of the elements  $p, q, f, H$  is zero; return **rej**.
2. Return **acc** if  $e(p, H) = e(q, f)$ ; return **rej** otherwise.

**Claim 1.2.** *Given  $p, q \in \mathbb{G}_1$  and  $f, H \in \mathbb{G}_2$ ,  $\text{SameRatio}((p, q), (f, H)) = \text{acc}$  if and only if there exists  $s \in \mathbb{F}_r^*$  such that  $(p, q)$  is a  $\mathbb{G}_1$ - $s$ -pair and  $(f, H)$  is a  $\mathbb{G}_2$ - $s$ -pair.*

*Proof.* Suppose that  $s \cdot p = q$  and  $s' \cdot f = H$ . Write  $p = a \cdot g_1, f = b \cdot g_2$  for some  $a, b \in \mathbb{F}_r$ . Note that if one of  $\{a, b, s, s'\}$  is 0, we return **rej** in the first step.

Otherwise, we have

$$e(p, H) = (a \cdot g_1, bs' \cdot g_2) = g_T^{abs'},$$

and

$$e(q, f) = (as \cdot g_1, b \cdot g_2) = g_T^{abs},$$

and thus  $\text{SameRatio}((p, q), (f, H)) = 1$  if and only if  $s = s' \pmod{r}$ . □

Let  $V = ((p_i, q_i))_{i \in [d]}$ , be a vector of pairs in  $\mathbb{G}_1$ . We say  $V$  is an  $s$ -vector in  $\mathbb{G}_1$  if for each  $i \in [d]$ ,  $(p_i, q_i)$  is a  $\mathbb{G}_1$ - $s$ -pair, or is equal to  $(0, 0)$ . We make the analogous definition for  $\mathbb{G}_2$ , and similarly to above, sometimes omit the group name when it is clear from the context what group the elements are in, simply using the term  $s$ -vector. In our protocol we often want to check if a long vector  $((p_i, q_i))_{i \in [d]}$  is an  $s$ -vector for some  $s \in \mathbb{F}_r^*$ . The next claim enables us to do so with just one pairing.

**Claim 1.3.** Suppose that  $((p_i, q_i))_{i \in [d]}$  is a vector of elements in  $\mathbb{G}_1 \setminus \{0\}$  that is not an  $s$ -vector. Choose random  $c_1, \dots, c_d \in \mathbb{F}_r$  and define

$$p \triangleq \sum_{i \in [d]} c_i \cdot p_i, \quad q \triangleq \sum_{i \in [d]} c_i \cdot q_i.$$

Then, with probability at least  $1 - 2/r$ , both  $(p, q) \neq (0, 0)$  and  $(p, q)$  is not an  $s$ -pair

*Proof.* Write  $p_i = a_i \cdot g_1$  for  $a_i \in \mathbb{F}_r$ , and  $q_i = s_i \cdot p_i$  for some  $s_i \in \mathbb{F}_r$ . Thus, we have  $p = a \cdot g_1$  for  $a \triangleq \sum_{i \in [d]} c_i a_i$  and  $q = b \cdot g_1$  for  $b \triangleq \sum_{i \in [d]} c_i a_i s_i$ . Let us assume  $a \neq 0$ . This happens with probability  $1 - 1/r$ . Write  $[d]$  as a disjoint union  $S \cup T$  where  $S$  is the set of indices of the  $s$ -pairs. That is  $S \triangleq \{i \in [d] \mid s_i = s\}$ . We have

$$b/a = \frac{\sum_{i \in [d]} c_i a_i s_i}{\sum_{i \in [d]} c_i a_i} = s + \frac{\sum_{i \in T} c_i \cdot (s - s_i)}{\sum_{i \in [d]} c_i a_i} = s + \frac{\sum_{i \in T} c_i \cdot (s - s_i)}{a}.$$

Thus,  $b/a = s$  if and only if the fraction in the right hand side is zero. As the numerator is a random combination of non-zero elements, this happens with probability  $1/r$ .

We conclude that with probability at least  $1 - 2/r$ ,  $(p, q)$  is not an  $s$ -pair □

Claim 1.3 implies the correctness of  $\text{sameRatio}(V, (f, H))$  that given an  $s$ -pair  $(f, H)$  in  $\mathbb{G}_2$ , checks whether  $V$  is an  $s$ -vector in  $\mathbb{G}_1$ .

$\text{sameRatio}(V = ((p_i, q_i))_{i \in [d]}, (f, H))$ :

1. If there exists a pair of the form  $(0, a)$  or  $(a, 0)$  for some  $a \neq 0$  in  $V$ ; return **rej**.
2. “Put aside” all elements of the form  $(0, 0)$ , and from now on assume all pairs in  $V$  are in  $\mathbb{G}_1 \setminus \{0\}$ . (If all pairs are of the form  $(0, 0)$  then return **acc**).
3. Choose random  $c_1, \dots, c_d \in \mathbb{F}_r$ .
4. Define  $p \triangleq \sum_{i \in [d]} c_i \cdot p_i$ , and  $q \triangleq \sum_{i \in [d]} c_i \cdot q_i$ .
5. If  $p = q = 0$ , return **acc**.
6. Otherwise, return  $\text{SameRatio}((p, q), (f, H))$ .

**Corollary 1.4.** Suppose  $\text{rp}_s$  in a  $\mathbb{G}_2$ - $s$ -pair, and  $V$  is a vector of pairs of  $\mathbb{G}_1$  elements. If  $V$  is an  $s$ -vector,  $\text{sameRatio}(V, \text{rp}_s)$  accepts with probability one. If  $V$  is not an  $s$ -vector,  $\text{sameRatio}(V, \text{rp}_s)$  accepts with probability at most  $2/r$ .

Let  $V$  be a vector of  $\mathbb{G}_1$ -elements and  $\text{rp}_s$  be a pair of  $\mathbb{G}_2$ -elements. We also use a method  $\text{sameRatioSeq}(V, \text{rp}_s)$  that given an  $s$ -pair  $\text{rp}_s$ , checks that each two consecutive elements of  $V$  are an  $s$ -pair. It does so by calling  $\text{sameRatio}(V', \text{rp}_s)$  with  $V' = ((V_0, V_1), (V_1, V_2), \dots, (V_{d-1}, V_d))$ .

## 1.2 Schnorr NIZKs for knowledge of discrete log

We review and define notation for using the well-known Schnorr protocol [Sch89]. Given an  $s$ -pair  $\text{rp}_s = (f, H = s \cdot f)$ , and a string  $h$ , we define the (randomized) string  $\text{NIZK}(\text{rp}_s, h)$  that can be interpreted as a proof that the generator of the string knows  $s$ .

NIZK( $\mathbf{rp}_s, h$ ):

1. Choose random  $a \in \mathbb{F}_r^*$  and let  $R := a \cdot f$ .
2. Let  $c := \text{COMMIT}(R \circ h)$  and interpret  $c$  as an element of  $\mathbb{F}_r^*$ , e.g. by taking its first  $\log r$  bits.
3. Let  $u := a + cs$ .
4. Define  $\text{NIZK}(\mathbf{rp}_s, h) := (R, u)$ .

Let us denote by  $\pi$  a string that is supposedly of the form  $\text{NIZK}(\mathbf{rp}_s, h)$ , for some string  $h$ .

$\text{VERIFY-NIZK}(\mathbf{rp}_s, \pi, h)$  is a boolean predicate that verifies that  $\pi$  is indeed of this form for the same given  $h$ .

VERIFY-NIZK( $(f, H), \pi, h$ ):

1. Let  $R, u$  be as in the description above.
2. Compute  $c := \text{COMMIT}(R \circ h)$ .
3. Return acc when  $u \cdot f = R + c \cdot H$ ; and rej otherwise.

### 1.3 The random-coefficient subprotocol

A large part of the protocol will consist of invocations of the *random-coefficient subprotocol*. In this subprotocol, we multiply a vector of  $\mathbb{G}_1$  elements coordinate-wise by the same scalar  $\alpha \in \mathbb{F}_r^*$ .  $\alpha$  here is a product of secret elements  $\{\alpha_i\}_{i \in [n]}$ , that we refer to later as *committed elements*. By this we mean, that before the subprotocol is invoked, for each  $i \in [n]$ ,  $P_i$  has broadcasted a  $\mathbb{G}_2$ - $\alpha_i$ -pair, denoted  $\mathbf{rp}_{\alpha_i}$ , that is accessible to the protocol verifier. (This will become clearer in the context of Section 2).

RCPC( $V, \alpha$ ):

**Common Input:** vector  $V \in \mathbb{G}_1^d$ .

**Individual inputs:** element  $\alpha_i \in \mathbb{F}_r^*$  for each  $i \in [n]$ .

**Output:** vector  $\alpha \cdot V \in \mathbb{G}_1^d$ , where  $\alpha = \prod_{i=1}^n \alpha_i$ .

1.  $P_1$  computes broadcasts  $V_1 := \alpha_1 \cdot V$ .
2. For  $i = 2, \dots, n$ ,  $P_i$  broadcasts  $V_i := \alpha_i \cdot V_{i-1}$ .
3. Players output  $V_n$  (which should equal  $\alpha \cdot V$ ).

Before discussing the transcript verification we define one more useful notation. For vectors  $S, T \in \mathbb{G}_1^d$  and a  $\mathbb{G}_2$ - $\alpha$ -pair  $\mathbf{rp}_\alpha$ ,  $\text{sameRatio}((S, T), \mathbf{rp}_\alpha)$  returns  $\text{sameRatio}(V, \mathbf{rp}_\alpha)$ , where  $V_i := (S_i, T_i)$ . The transcript verification procedure receives as input  $V, V_1, \dots, V_n$ , and for each  $i \in [n]$ , the  $\mathbb{G}_2$ - $\alpha_i$ -pair,  $\mathbf{rp}_{\alpha_i}$ .

verifyRCPC( $V, \alpha$ ):

**Input:**  $V$ , protocol transcript  $V_1, \dots, V_n \in \mathbb{G}_1^d$ , for each  $i \in [n]$  a  $\mathbb{G}_2$ - $\alpha_i$ -pair  $\text{rp}_{\alpha_i}$ .

**Output:** acc or rej.

1. Run `sameRatio`(( $V, V_1$ ),  $\text{rp}_{\alpha_1}$ ).
2. For  $i = 2, \dots, n$ , run `sameRatio`(( $V_{i-1}, V_i$ ),  $\text{rp}_{\alpha_i}$ ).
3. Return acc if all invocations returned acc; and return rej otherwise.

From the correctness of the `sameRatio`(, ) method (Corollary 1.4) we have that

**Claim 1.5.** *If the players follow the protocol correctly, the output is  $\alpha \cdot V$ , and transcript verification outputs acc with probability one. Otherwise, transcript verification outputs acc with probability at most  $2/r$ .*

## 2 Protocol description

**The participants** The protocol is conducted by  $n$  players, a coordinator, and a protocol verifier. In the implementation the role of the coordinator and protocol verifier can be played by the same server. We find it useful to separate these roles, though, as the actions of the protocol verifier may be executed only after the protocol has terminated, if one wishes to reduce the time the players have to be engaged. Moreover, any party wishing to check the validity of the transcript and generated parameters can do so solely with access to the protocol transcript. On the other hand, this has the disadvantage that non-valid messages will be detected only in hindsight, and the whole process will have to be restarted if one wishes to generate valid SNARK parameters.

Similarly, the role of the coordinator is not strictly necessary if one assumes a blackboard model where each player sees all messages broadcasted. (In our actual implementation the coordinator passes messages between the players). Our security analysis holds when all messages are seen by all players. However, even in such a blackboard model there is an advantage of having of a coordinator role: At the beginning of Round 3 a heavy computation needs to be performed (Subsection 2.3) that in theory could be performed by the first player before he sends his message for that round. However, as this heavy computation does not require access to any secrets of the players, having the coordinator perform it can save much time, if the coordinator is run on a strong server, and the players have weaker machines.

The protocol consists of four “round-robin” rounds, where for each  $i \in [n]$ , player  $P_i$  can send his message after receiving the message of  $P_{i-1}$ .  $P_1$  can send his message after receiving an “initializer message” from the coordinator, which is empty in some of the rounds. An exception of this is the first round, where all players may send their message to the coordinator in parallel. However, security is not harmed if a player sees other players’ messages before sending his in that round. Round 2 is divided into several parts for clarity, however the messages of a player  $P_i$  in all parts of that round can be sent in parallel. Similarly, Round 3 and 4 consist of several one round round-robin subprotocols; however, the messages of a player  $P_i$  in all these subprotocols can be sent in parallel.

## 2.1 Round 1: commitments

For each  $i \in [n]$ ,  $P_i$  does the following.

1. Generate a set of uniform elements in  $\mathbb{F}_r^*$

$$\text{secrets}_i := \{\tau_i, \rho_{A,i}, \rho_{B,i}, \alpha_{A,i}, \alpha_{B,i}, \alpha_{C,i}, \beta_i, \gamma_i\}.$$

Omitting the index  $i$  for readability from now on, let

$$\begin{aligned} \text{elements}_i := \{ & \tau, \rho_A, \rho_B, \alpha_A, \alpha_B, \alpha_C, \beta, \gamma, \rho_A \alpha_A, \rho_B \alpha_B, \\ & \rho_A \rho_B, \rho_A \rho_B \alpha_C, \beta \gamma \} \end{aligned}$$

2. Now  $P_i$  generates the set of group elements<sup>1</sup>

$$\mathbf{e}_i := (\tau, \rho_A, \rho_A \rho_B, \rho_A \alpha_A, \rho_A \rho_B \alpha_B, \rho_A \rho_B \alpha_C, \gamma, \beta \gamma) \cdot g.$$

3.  $P_i$  computes  $h_i := \text{COMMIT}(\mathbf{e}_i)$  and broadcasts  $h_i$ .

## 2.2 Round 2

### Part 1: Revealing commitments

For each  $i \in [n]$

1.  $P_i$  broadcasts  $\mathbf{e}_i$ .
2. The protocol verifier checks that indeed  $h_i = \text{COMMIT}(\mathbf{e}_i)$ .

**Committed elements** From the end of Round 2, part 1 of the protocol, we refer to the elements of  $\text{elements}_i$  for some  $i \in [n]$  as *committed elements*. The reason is that by this stage of the protocol, for each  $s \in \text{elements}_i$ ,  $P_i$  has sent an  $s$ -pair in both  $\mathbb{G}_1$  and  $\mathbb{G}_2$ , effectively committing him to the value of  $s$ . For each such element  $s$ , we refer to the  $s$ -pair in  $\mathbb{G}_1$  by  $\text{rp}_s$  and the  $s$ -pair in  $\mathbb{G}_2$  by  $\text{rp}_s^2$ . We list the corresponding elements and  $s$ -pairs, omitting the  $i$  subscript for readability:

- $\tau$ :  $(\text{rp}_\tau^1, \text{rp}_\tau^2) = (g, \tau \cdot g)$ .
- $\rho_A$ :  $(\text{rp}_{\rho_A}^1, \text{rp}_{\rho_A}^2) = (g, \rho_A \cdot g)$ .
- $\rho_B$ :  $(\text{rp}_{\rho_B}^1, \text{rp}_{\rho_B}^2) = (g, \rho_B \cdot g)$ .
- $\alpha_A$ :  $(\text{rp}_{\alpha_A}^1, \text{rp}_{\alpha_A}^2) = (\rho_A \cdot g, \rho_A \alpha_A \cdot g)$ .
- $\alpha_B$ :  $(\text{rp}_{\alpha_B}^1, \text{rp}_{\alpha_B}^2) = (\rho_A \rho_B \cdot g, \rho_A \rho_B \alpha_B \cdot g)$ .
- $\alpha_C$ :  $(\text{rp}_{\alpha_C}^1, \text{rp}_{\alpha_C}^2) = (\rho_A \rho_B \cdot g, \rho_A \rho_B \alpha_C \cdot g)$ .

---

<sup>1</sup>In the actual code a more complex set of elements is used that can be efficiently derived from  $\text{elements}_i$ , as described in Appendix A. The reason we use the more complex set is that it potentially provides more security as it contains less information about  $\text{secrets}_i$ . However, the proof works as well with this definition of  $\mathbf{e}_i$  and it provides a significantly simpler presentation. We explain in Appendix A the slight modification for protocol and proof for using the more complex element set.

- $\beta$ :  $(\text{rp}_\beta^1, \text{rp}_\beta^2) = (\gamma \cdot g, \beta\gamma \cdot g)$ .
- $\gamma$ :  $(\text{rp}_\gamma^1, \text{rp}_\gamma^2) = (g, \gamma \cdot g)$ .
- $\rho_A\alpha_A$ :  $(\text{rp}_{\rho_A\alpha_A}^1, \text{rp}_{\rho_A\alpha_A}^2) = (g, \rho_A\alpha_A \cdot g)$ .
- $\rho_B\alpha_B$ :  $(\text{rp}_{\rho_B\alpha_B}^1, \text{rp}_{\rho_B\alpha_B}^2) = (\rho_A \cdot g, \rho_A\rho_B\alpha_B \cdot g)$ .
- $\rho_A\rho_B$ :  $(\text{rp}_{\rho_A\rho_B}^1, \text{rp}_{\rho_A\rho_B}^2) = (g, \rho_A\rho_B \cdot g)$ .
- $\rho_A\rho_B\alpha_C$ :  $(\text{rp}_{\rho_A\rho_B\alpha_C}^1, \text{rp}_{\rho_A\rho_B\alpha_C}^2) = (g, \rho_A\rho_B\alpha_C \cdot g)$ .
- $\beta\gamma$ :  $(\text{rp}_{\beta\gamma}^1, \text{rp}_{\beta\gamma}^2) = (g, \beta\gamma \cdot g)$ .

Of course, we need to check that  $P_i$  has committed to the *same* element  $s \in \mathbb{F}_r^*$  by  $\text{rp}_s$  and  $\text{rp}_s^2$ . This is done by the protocol verifier in the next stage.

### Part 2: Checking commitment consistency

For each  $i \in [n]$ , and  $s \in \text{elements}_i$ , the protocol verifier runs  $\text{SameRatio}(\text{rp}_s, \text{rp}_s^2)$ , and outputs  $\text{rej}$  if any invocation returned  $\text{rej}$ .

### Part 3: Proving and verifying knowledge of discrete logs

Let  $h := \text{COMMIT}(h_1 \circ \dots \circ h_n)$  be the hash of the transcript of Round 1.  $P_1$  computes and broadcasts  $h$ .

For each  $i \in [n]$

1. For  $s \in \text{secrets}_i$ , let  $h_{i,s} := \text{COMMIT}(h \circ \text{rp}_s^1)$ . Note that both  $P_i$  and the protocol verifier, seeing the transcript up to this point, can efficiently compute the elements  $\{h_{i,s}\}$ .
2. For each  $s \in \text{secrets}_i$ ,  $P_i$  broadcasts  $\pi_{i,s} := \text{NIZK}(\text{rp}_s^1, h_{i,s})$ .
3. The protocol verifier checks for each  $s \in \text{secrets}_i$  that  $\text{VERIFY-NIZK}(\text{rp}_s^1, \pi_{i,s}, h_{i,s}) = \text{acc}$ .

### Part 4: The random powers subprotocol:

The purpose of the subprotocol is to output the vector

$$\text{POWERS}_\tau := \left( (1, \tau, \tau^2, \dots, \tau^d) \cdot g_1, (1, \tau, \tau^2, \dots, \tau^d) \cdot g_2 \right),$$

where  $\tau := \tau_1 \cdots \tau_n$ . Recall that  $\tau_1, \dots, \tau_n$  are committed values from Round 1.

For a vector  $V \in \mathbb{G}_1^{d+1}$ , and  $a \in \mathbb{F}_r$ , we use below the notation  $\text{powerMult}(V, a) \in \mathbb{G}_1^{d+1}$ , defined as

$$\text{powerMult}(V, a)_i \triangleq a^i \cdot V_i,$$

for  $i \in \{0, \dots, d\}$ . We use the analogous notation for a vector  $V \in \mathbb{G}_2^{d+1}$ .

### Phase 1: Computing power vectors

1.  $P_1$  does the following.
  - (a) Computes  $V_1 = (1, \tau_1, \tau_1^2, \dots, \tau_1^d) \cdot g_1$  and  $V'_1 = (1, \tau_1, \tau_1^2, \dots, \tau_1^d) \cdot g_2$ .
  - (b) Broadcasts  $(V_1, V'_1)$ .
2. For  $i = 2, \dots, n$ ,  $P_i$  does the following:
  - (a) Compute  $V_i \triangleq \text{powerMult}(V_{i-1}, \tau_i)$  and  $V'_i \triangleq \text{powerMult}(V'_{i-1}, \tau_{i-1})$ .
  - (b) Broadcasts  $(V_i, V'_i)$ .

**Phase 2: Checking power vectors are valid** The protocol verifier performs the following checks<sup>2</sup> on the broadcasted data from Phase 1:

1. Check that
 
$$\text{sameRatioSeq}(V_1, \text{rp}_{\tau_1}^2),$$
 and
 
$$\text{sameRatioSeq}(V'_1, (V_{1,0}, V_{1,1}))$$
2. For each  $i \in [n] \setminus \{1\}$  check that
 
$$\text{sameRatioSeq}(V_i, (V'_{i,0}, V'_{i,1})),$$

$$\text{sameRatioSeq}(V'_i, (V_{i,0}, V_{i,1})),$$
 and
 
$$\text{SameRatio}((V_{i-1,1}, V_{i,1}), \text{rp}_{\tau_i}^2)$$

The protocol verifier rejects the transcript if one of the checks failed; otherwise, the coordinator defines  $(PK_H \triangleq V_n, PK'_H \triangleq V'_n)$  is taken as the subprotocol output.

### 2.3 Coordinator after Round 2: Computing Lagrange basis using FFT, and preparing the vectors $\vec{A}, \vec{B}$ and $\vec{C}$

To avoid a quadratic proving time the polynomials in the QAP must be evaluated in a Lagrange basis. There seems to be no way of directly computing a Lagrange basis at  $\tau$  in a 1-round MPC in a similar way we did for the standard basis in the Random-Powers subprotocol. Thus we will do ‘FFT in the coefficient’ to compute the Lagrange basis on the output of the random-powers subprotocol. Details and definitions follow. Let  $\omega \in \mathbb{F}_r$  be a primitive root of unity of order  $d = 2^\ell$ , in code  $d$  is typically the first power of two larger or equal to the circuit size.

For  $i = 1, \dots, d$ , we define  $L_i$  to be the  $i$ 'th Lagrange polynomial over the points  $\{\omega^i\}_{i \in [d]}$ . That is,  $L_i$  is the unique polynomial of degree smaller than  $d$ , such that  $L_i(\omega^i) = 1$  and  $L_i(\omega^j) = 0$ , for  $j \in [d] \setminus \{i\}$ .

<sup>2</sup>The checks below could be simplified if we had also used  $\text{rp}_{\tau_i}^1$ . We do not use it as in the actual code, as explained in Appendix A, we do not have a  $\mathbb{G}_{1-\tau_i}$ -pair.



**Claim 2.1.** For  $i \in [d]$  we have

$$L_i(X) := c_d \cdot \sum_{j=0}^{d-1} (X/\omega^i)^j,$$

for  $c_d := \frac{1}{d}$ .

*Proof.* Substituting  $X = \omega^{i'}$  for  $i' \neq i$  we have a sum over all roots of unity of order  $d$  which is 0. Substituting  $X = \omega^i$  we have a sum of  $d$  ones divided by  $d$  which is one.  $\square$

For  $\tau \in \mathbb{F}_r^*$ , denote by we denote by  $\text{LAG}_\tau \in \mathbb{G}_1^d \times \mathbb{G}_2^d$  the vector

$$\text{LAG}_\tau := ((L_i(\tau) \cdot g_1)_{i \in [d]}, (L_i(\tau) \cdot g_2)_{i \in [d]}).$$

The purpose of the FFT-protocol is to compute  $\text{LAG}_\tau$  from  $\text{POWERS}_\tau$ . Let us focus for simplicity how to compute the first half containing the  $\mathbb{G}_1$  elements. Computing the second half is completely analogous. We define the polynomial  $P(Y) (= P_\tau(Y))$  by

$$P(Y) := \sum_{j=0}^{<d} (\tau \cdot Y)^j.$$

It is easy to check that

**Claim 2.2.** For  $i \in [d]$

$$L_i(\tau) = P(\omega^{-i}) = P(\omega^{d-i}),$$

and thus

$$\text{LAG}_\tau = (P(\omega^{-i}))_{i \in [d]} \cdot g$$

Thus our task reduces to computing the vector  $(P(\omega^i))_{i \in [d]} \cdot g_1$  (and then reordering accordingly). We describe an algorithm to compute the vector  $(P(\omega^i))_{i \in [d]}$  using the vector  $(1, \tau, \tau^2, \dots, \tau^d)$  as input and only linear combination gates. This suffices as these linear combinations can be simulated by scalar multiplication and addition in  $\mathbb{G}_1$ , when operating on  $\text{POWERS}_\tau$ . We proceed to review standard FFT tricks that will be used.

For a polynomial  $P(Y) = \sum_{i=0}^{<d} a_i \cdot Y^i$  of degree smaller than  $d$ , where  $d$  is even, we define the polynomials

$$P_{\text{EVEN}}(Y) := \sum_{i=0}^{<d/2} a_{2i} \cdot Y^i,$$

and

$$P_{\text{ODD}}(Y) := \sum_{i=0}^{<d/2} a_{2i+1} \cdot Y^i.$$

It is easy to see that

$$P(Y) = P_{\text{EVEN}}(Y^2) + Y \cdot P_{\text{ODD}}(Y^2).$$

In particular, for  $i \in [d]$

$$P(\omega^i) = P_{\text{EVEN}}(\omega^{2i}) + \omega^i \cdot P_{\text{ODD}}(\omega^{2i})$$

For  $j = 0, \dots, \ell - 1$  denote  $\omega_j \triangleq \omega^{2^j}$ . Note further that  $\{\omega^{2^i}\}_{i \in [d]}$  is a subgroup of size  $d/2$  generated by  $\omega_1$ . More generally, for  $j = 1, \dots, \ell - 1$   $\{\omega_{j-1}^{2^i}\}_{i \in [d]}$  is a subgroup of size  $2^{d-j}$  generated by  $\omega_j$ . The above discussion suggests the following (well-known FFT) recursive algorithm.

**FFT**

**input:** Polynomial  $P$ , given as list of coefficients, element  $\omega \in \mathbb{F}_r$  generating a group of size  $d = 2^\ell$ .

**output:** The vector  $V = (P(\omega^i))_{i \in [d]}$ .

1. If  $d = 2$  compute  $V$  directly.
2. Otherwise,
  - (a) Call the method recursively twice; first with  $P_{\text{EVEN}}$  and  $\omega^2$  to obtain output  $E := (P_{\text{EVEN}}(\omega^{2i}))_{i \in [d/2]}$ , and then with  $P_{\text{ODD}}$  and  $\omega^2$  to obtain the vector  $O := (P_{\text{ODD}}(\omega^{2i}))_{i \in [d/2]}$ .
  - (b) Compute the vector  $V$  using  $E, O$  and the equality mentioned above. More specifically, each element  $V_i$  of  $V$  is computed as

$$V_i = P(\omega^i) = P_{\text{EVEN}}(\omega^{2i}) + \omega^i \cdot P_{\text{ODD}}(\omega^{2i}) = E_i + \omega^i \cdot O_i,$$

(where we subtract  $d/2$  from indices of  $E$  and  $O$  when they are larger than  $d/2$ ).

In summary, we obtain  $\text{LAG}_\tau$  by applying the FFT and the polynomial  $P$  described above, with coefficients  $1, \tau, \dots, \tau^{d-1}$  and an  $\omega$  of order  $d$  - which should be the same  $\omega$  used in the QAP construction. After getting the result from the FFT, we reverse the order of the vector and multiply each element by the scalar  $1/d$ .

**Preparing the vectors  $\vec{A}, \vec{B}$  and  $\vec{C}$**  We need to compute the vectors  $\vec{A} := (A_i(\tau))_{i \in [0..m+1]} \cdot g_1$ ,  $\vec{B} := (B_i(\tau))_{i \in [0..m+1]} \cdot g_1$ ,  $\vec{B}_2 := (B_i(\tau))_{i \in [0..m+1]} \cdot g_2$ , and  $\vec{C} := (C_i(\tau))_{i \in [0..m+1]} \cdot g_1$ . Note that<sup>3</sup>  $A_{m+1} = B_{m+1} = C_{m+1} := Z[\tau] \cdot g_1 = (\tau^d - 1) \cdot g_1$ . After the FFT, we have obtained  $\text{LAG}_\tau$ , so each such element is a linear combination of elements of  $\text{LAG}_\tau$ ; except  $Z(\tau) \cdot g$ , that can be computed using the elements  $\tau^d \cdot g$  in  $\text{POWERS}_\tau$ .

## 2.4 Round 3

After the random-powers subprotocol and the FFT, the MPC consists of a few invocations of the random-coefficient subprotocol. These invocations add a total of two rounds to the MPC, as sometimes and random-coefficient subprotocol will need the output of a previous random-coefficient subprotocol as input.

**Part 1: broadcasting result of FFT** The coordinator broadcasts the vectors  $\vec{A}, \vec{B}, \vec{C}, \vec{B}_2$ .

---

<sup>3</sup>A small technicality is that in [BCTV14]  $Z(\tau) \cdot g_2$  is appended with index  $m+2$  in  $\vec{B}_2$ , and  $Z(\tau) \cdot g_1$  is appended in index  $m+3$  in  $\vec{C}$ . However in the actual libsnark code, they are appended in index  $m+1$ , and the prover algorithm is slightly modified to take this into account.

**Part 2: Random coefficient subprotocol invocations** We apply the random-coefficient subprotocol numerous times to obtain the different key elements. For an element  $\alpha_i \in \text{elements}_i$ , we abuse notation here and denote  $\alpha := \alpha_1 \cdots \alpha_n$  (as opposed to omitting the index  $i$  and writing  $\alpha$  for  $\alpha_i$  which we did when describing Round 1).

1.  $PK_A = \text{RCPC}(\vec{A}, \rho_A)$ .
2.  $PK_B = \text{RCPC}(\vec{B}_2, \rho_B)$ .
3.  $PK_C = \text{RCPC}(\vec{C}, \rho_A \rho_B)$ .
4.  $PK'_A = \text{RCPC}(\vec{A}, \rho_A \alpha_A)$
5.  $PK'_B = \text{RCPC}(\vec{B}, \rho_B \alpha_B)$ .
6.  $PK'_C = \text{RCPC}(\vec{C}, \rho_A \rho_B \alpha_C)$
7.  $temp_B = \text{RCPC}(\vec{B}, \rho_B)$
8.  $VK_Z = \text{RCPC}(g_2 \cdot Z(\tau), \rho_A \rho_B)$ . We use that  $g_2 \cdot Z(\tau) = g_2 \cdot (\tau^d - 1)$  can be computed from  $PK'_H$  that was computed in Round 2, part 2, as described in Section 2.2.
9.  $VK_A = \text{RCPC}(g_2, \alpha_A)$ .
10.  $VK_B = \text{RCPC}(g_1, \alpha_B)$ .
11.  $VK_C = \text{RCPC}(g_2, \alpha_C)$ .

## 2.5 Round 4: Computing key elements involving $\beta$ , especially $PK_K$

Each player (or just the coordinator) computes  $V := PK_A + temp_B + PK_C$ . The players compute

1.  $PK_K = \text{RCPC}(V, \beta)$
2.  $VK_\gamma = \text{RCPC}(g_2, \gamma)$
3.  $VK_{\beta\gamma}^1 = \text{RCPC}(g_1, \beta\gamma)$ .
4.  $VK_{\beta\gamma}^2 = \text{RCPC}(g_2, \beta\gamma)$ .

Finally, the protocol verifier will run  $\text{verifyRCPC}(\cdot)$  on the input and transcript of each subprotocol executed in Round 3 or 4; and output acc if and only if all invocations of  $\text{verifyRCPC}(\cdot)$  returned acc.

## 3 Security proof

Fix a QAP instance  $\phi$  and input  $x$  for  $\phi$ . Let  $V$  be the snark verifier of [PHGR16]. We denote by  $T \subset [n]$ ,  $|T| = n - 1$ , the subset of players controlled by the adversary  $B$ . Our goal is to show that under certain cryptographic assumptions, most notably the Knowledge of Exponent (KEA) assumption, if  $B$  can generate a proof that  $V(\phi, x)$  accepts with non-negligible probability, when  $V$  is using the parameters generated in the protocol, then there exists an extractor  $E$  generating a witness  $\omega$  satisfying  $(\phi, x)$  with non-negligible probability.

**Notational conventions** To simplify notations we will refer to a fixed pair of groups  $(\mathbb{G}_1, \mathbb{G}_2)$  of order  $r$ ; we implicitly assume that we have a generator  $\mathcal{G}$  that when given integer  $t$  as parameter, returns a prime  $r$  with  $r = \text{poly}(t)$  and groups  $\mathbb{G}_1, \mathbb{G}_2, \mathbb{G}_t$  of order  $r$ , with the property that for all cryptographic problems described next (Knowledge of Exponent, Strong Diffie-Helman, Power Diffie-Helman) an efficient adversary has  $\text{negl}(\log r)$  success probability; where we remind that by efficient adversary we mean a non-uniform (sequence of) circuit(s) of size  $\text{poly}(\log r)$ .

### 3.1 Cryptographic assumptions

We use bilinear versions of the Strong Diffie-Helman, Power Diffie-Helman, and Knowledge of Exponent assumption as in [CFH<sup>+</sup>15]. It will be convenient to denote  $G^* := \mathbb{G}_1 \setminus \{0\} \times \mathbb{G}_2 \setminus \{0\}$ , and as before by  $g = (g_1, g_2)$  a pair of generators for both groups.

**Definition 3.1** (Knowledge of Exponent Assumption (KEA)). *For any efficient  $A$  there exists an efficient  $E$  such that the following holds. Fix positive integer  $d$ , and an efficient randomized circuit  $S$  with input domain  $(G^*)^{2(d+1)}$ . Consider the following experiment.*

*$\tau, \alpha \in \mathbb{F}_r^*$  and  $g \in G^*$  are chosen uniformly. We denote  $V := (1, \tau, \dots, \tau^d, \alpha, \alpha\tau, \dots, \alpha\tau^d) \cdot g$ . Then  $A$  is given as input  $S(V)$ ; and outputs a pair of the form  $(c, d)$  in  $\mathbb{G}_1 \setminus \{0\}$ , which he “hopes” is of the form  $(c, \alpha c)$ .  $E$ , given the same input, outputs  $a_0, a_1, \dots, a_d \in \mathbb{F}_r$  such that the probability that both*

1.  $A$  “succeeded”, i.e.,  $d = \alpha \cdot c$ . But,
2.  $E$  “failed”, i.e.,  $c \neq (\sum_{i=0}^d a_i \tau^i) \cdot g_1$ .

*is  $\text{negl}(\log r)$ . The same holds when  $\mathbb{G}_1 \setminus \{0\}$  is replaced by  $\mathbb{G}_2 \setminus \{0\}$  and  $g_1$  is replaced by  $g_2$ .*

**Remark 3.2.** *Bitansky et. al [BCPR14], in fact show that the above assumption is false, assuming the existence of indistinguishability obfuscation, when allowing a general  $S$ . If one is troubled by this, one may replace the general  $S$  in the above definition, by limiting  $S$  to be a circuit that computes one of the functions in Claim 3.5, after choosing some of its inputs (besides the instance  $\phi$ ) uniformly. We preferred to stick with the less cumbersome definition above, particularly, as the existence of indistinguishability obfuscation is questionable.*

**Definition 3.3** ( $q$ -SDH assumption). *Fix positive integer  $q$ . Consider the following experiment.  $\tau \in \mathbb{F}_r^*$  and  $g \in G^*$  are chosen uniformly. Then an efficient  $A$  is given as input  $(1, \tau, \dots, \tau^q) \cdot g$ . Then the probability that  $A$  outputs  $e(g_1, g_2)^{\frac{1}{\tau+c}}$ , for some  $c \in \mathbb{F}_r^*$  is  $\text{negl}(\log r)$ .*

**Definition 3.4** ( $q$ -PDH assumption). *Fix positive integer  $q$ . Consider the following experiment.  $\tau \in \mathbb{F}_r^*$  and  $g \in G^*$  are chosen uniformly. Then an efficient  $A$  is given as input  $(1, \tau, \dots, \tau^q, \tau^{q+2}, \dots, \tau^{2q}) \cdot g$ . Then the probability that  $A$  outputs  $\tau^{q+1} \cdot g_1$  is  $\text{negl}(\log r)$ .*

### 3.2 The Pinocchio Theorem

We refer to Appendix B of [BCTV14] for a description of the Pinocchio protocol [PHGR16] with notation close to what is used here. Furthermore, one may refer to [PHGR16] and [BCTV14] for definitions relating to quadratic arithmetic programs (QAPs), that we assume familiarity with here. Given a QAP instance  $\phi$  of degree  $d$ , we typically denote by  $\text{params}_\phi$  a legitimate set of Pinocchio

parameters, i.e., proving key and verification key, for  $\phi$ . We can think of  $\text{params}_\phi$  as a deterministic function of the values  $\tau, \rho_A, \rho_B, \alpha_A, \alpha_B, \alpha_C, \gamma, \beta \in \mathbb{F}_r^*$ ; or alternatively of a vector  $\text{secrets} \in (\mathbb{F}_r^*)^8$  consisting of these values. Actually, for our security proof we need to define  $\text{params}_\phi$  to include all Pinocchio key elements “given in both groups”. Specifically, denoting  $g := (g_1, g_2)$ ,

$$\text{params}_\phi(\text{secrets}) := (P_H, P_\phi, P_{\alpha\phi}, P_K, V),$$

where  $P_H := \{\tau^i \cdot g\}_{i \in [d]}$ ,  $P_\phi := (P_A, P_B, P_C)$ ,  $P_{\alpha\phi} := (P_{\alpha_A}, P_{\alpha_B}, P_{\alpha_C})$ ,  $P_K := \beta \cdot (P_A + P_B + P_C)$ , where

$$P_A := (A_i \cdot g_A)_{i \in [m]}, P_{\alpha_A} := (A_i \alpha_A \cdot g_A)_{i \in [m]},$$

and  $P_B, P_{\alpha_B}, P_C, P_{\alpha_C}$  defined similarly, where  $g_A := \rho_A \cdot g$ ,  $g_B := \rho_B \cdot g$  and  $g_C := \rho_A \rho_B \cdot g$ , and <sup>4</sup>

$$V := (\tau, \rho_A, \rho_A \rho_B, \rho_A \alpha_A, \rho_A \rho_B \alpha_B, \rho_A \rho_B \alpha_C, \gamma, \beta \gamma) \cdot g$$

The following claim enables us to use the knowledge of exponent assumption in the proof of Theorem 3.6.

**Claim 3.5.** *There are efficient (deterministic) functions  $F_A, F_B, F_C$  such that the following holds. Fix any vector  $\text{secrets} = (\tau, \rho_A, \rho_B, \alpha_A, \alpha_B, \alpha_C, \gamma, \beta)$  in  $(\mathbb{F}_r^*)^8$  and instance  $\phi$ . Denote by  $\text{secrets}_A, \text{secrets}_B$  and  $\text{secrets}_C$  the vector secrets when omitting the element  $\alpha_A, \alpha_B$  and  $\alpha_C$  respectively. Then*

$$\begin{aligned} \text{params}_\phi(\text{secrets}) &= F_A(P_H, P_H \cdot \alpha_A, \text{secrets}_A, \phi) \\ &= F_B(P_H, P_H \cdot \alpha_B, \text{secrets}_B, \phi) = F_C(P_H, P_H \cdot \alpha_C, \text{secrets}_C, \phi) \end{aligned}$$

*Proof.* By simple examination of the elements of  $\text{params}_\phi(\text{secrets})$ . For example, the only elements in  $\text{params}_\phi(\text{secrets})$  that are not a function of  $\text{secrets}_A$  are  $P_{\alpha_A}$  and  $\rho_A \alpha_A \cdot g \in V$ . Both are a joint efficient function of  $\rho_A$  and  $P_H \cdot \alpha_A$ : We can compute  $P_H \cdot \alpha_A \cdot \rho_A = \{\tau^i \rho_A \alpha_A \cdot g\}_{i \in [d]}$  and then  $P_{\alpha_A}$  elements are linear combinations of elements of this vector, and  $\rho_A \alpha_A \cdot g$  is simply the first element of this vector. □

Recall that  $V$  denotes the Pinocchio protocol verifier. The inputs of  $V$  include the QAP instance  $\phi$ , the instance input  $x$ , the CRS or public parameters  $\text{params}_\phi$ , and the purported proof  $\pi$  that indeed  $x$  satisfies  $\phi$ , and that the prover knows a witness showing this. A slight modification of the security proof of [PHGR16] shows that

**Theorem 3.6.** *[Pinocchio proof of knowledge] For any efficient  $A$  there exists an efficient extractor  $E$  such that for any instance  $\phi$  and input  $x$  the following holds. The probability over  $\text{secrets} \in (\mathbb{F}_r^*)^8$ , when  $A$  and  $E$  are given  $(\phi, x)$  and  $\text{params}_\phi(\text{secrets})$  as input that*

1.  $A$  produces  $\pi$  such that  $V(\phi, x, \text{params}_\phi(\text{secrets}), \pi) = \text{acc}$ , but
2.  $E$  does not output a witness  $\omega$  satisfying  $(\phi, x)$ ,

is  $\text{negl}(\log r)$ .

---

<sup>4</sup>The actual verification key  $V$  in fact contains less information that can be derived from  $V$  as defined here.

The proof is almost identical to that of [PHGR16], but we present it here for completeness, at times referring to [PHGR16] for details. An advantage of this proof is that it works for the variant of Pinocchio actually implemented in libsnark, as described in Appendix B of [BCTV14]. To our knowledge, no proof for this variant is written elsewhere. We also recommend looking at the proofs of [GGPR13, CFH<sup>+</sup>15] for intuition and clarifications.

*Proof.* We are given  $A$  and wish to construct  $E$ . We describe how  $E$  operates given inputs  $(\phi, x)$  and  $\text{params}_\phi(\text{secrets})$ . Recall that the purported proof  $\pi$  produced by  $V$  has the structure, in the notation of [BCTV14],

$$\pi = (\pi_A, \pi_B, \pi_C, \pi'_A, \pi'_B, \pi'_C, \pi_K, \pi_H).$$

From the description of  $V$ , we know that whenever  $A$  produces a proof  $\pi$  accepted by  $V$ , we have in particular,  $\pi'_A = \alpha_A \cdot \pi_A$ ,  $\pi'_B = \alpha_B \cdot \pi_B$  and  $\pi'_C = \alpha_C \cdot \pi_C$ , where  $\alpha_A, \alpha_B, \alpha_C$  are the corresponding elements of the vector  $\text{secrets}$ .  $E$  works as follows. It gives  $\text{params}_\phi(\text{secrets})$  as input to the extractors  $E_A, E_B, E_C$  that exist by the KEA assumption together with Claim 3.5. Let  $a_0, \dots, a_d$  be  $E_A$ 's output. Define  $A_{\text{mid}}(X) := \sum_{i=0}^d a_i \cdot X^i$ . Let  $A_{io}$  be the polynomial of degree at most  $d$  defined by the  $io$  elements in  $x$ ; i.e., when  $x = (c_1, \dots, c_n)$ ,  $A_{io}(X) := A_0(X) + \sum_{i=1}^n c_i \cdot A_i(X)$ . Define  $A(X) := A_{io}(X) + A_{\text{mid}}(X)$ .  $E$  does an analogous thing with  $E_B$  and  $E_C$  to obtain polynomials  $B, C$ . Now, using linear algebra,  $E$  determines whether there exists a set of coefficients  $c = (c_0 = 1, c_1, \dots, c_m)$ , such that

$$A(X) = \sum_{i=0}^m c_i \cdot A_i(X), B(X) = \sum_{i=0}^m c_i \cdot B_i(X), C(X) = \sum_{i=0}^m c_i \cdot C_i(X).$$

From the non-degeneracy property<sup>5</sup> [BCTV14], it follows that if there exists such  $c$  it coincides with  $x$  on  $c_1, \dots, c_n$ . If such  $c$  exists, output any such  $c$  as the proposed QAP witness  $\omega$  for  $(\phi, x)$ . Otherwise, abort. Let  $\eta$  be the probability that  $A$  produced a valid proof but  $E$  did not produce a valid assignment for  $(\phi, x)$ . Let  $q := 4d + 4$ . We construct an efficient  $B$  with the following property. Given a challenge  $\text{challenge} = \text{challenge}_s := (1, s, \dots, s^q, s^{q+2}, \dots, s^{2q}) \cdot g$ , where  $s$  is uniform in  $\mathbb{F}_r^*$ ,  $B$  outputs with probability  $\eta - \text{negl}(\log r)$  either

- $s^{q+1} \cdot g_1$ , or
- $e(g_1, g_2)^{\frac{1}{s+t}}$ , for some  $t \in \mathbb{F}_r^*$ .

This implies that  $\eta = \text{negl}(\log r)$ , as otherwise it would contradict the  $2q - SDH$  or  $q - PDH$  assumption. Thus, showing  $\eta = \text{negl}(\log r)$  suffices to prove the theorem.<sup>6</sup>

**Description of  $B$ :** Given  $\text{challenge}$ ,  $B$  begins by constructing a valid set of parameters  $\text{params}^{\text{pin}}$ , that are a randomized function  $\text{params}^{\text{pin}}(s)$  of  $s \in \mathbb{F}_r^*$ , as follows.

1.  $\alpha_A, \alpha_B, \alpha_C, \rho'_A, \rho'_B, \gamma'$  are chosen uniformly in  $\mathbb{F}_r^*$

<sup>5</sup>One needs to make a stronger definition of non-degeneracy than given in [BCTV14]. Specifically, we require that  $A_0, \dots, A_n$  are linearly independent *and* their span is disjoint from the span of  $\{A_{n+1}, \dots, A_m\}$  except for 0.

<sup>6</sup>For the completely precise argument one must also choose  $g \in G^*$  randomly and take success probability over that. To avoid having to “carry the  $g$ ”, we implicitly assume that whenever a statement is made about fixed  $g$  it happens with non-negligible probability over a uniform choice of  $g$ . e.g. in the theorem statement we are actually assuming  $A$  produces a valid proof for  $(\phi, x, \text{params}_\phi(\text{secrets}))$  with probability  $\delta$ , for a non-negligible fraction of  $g \in G^*$ .

2. We define  $\rho_A := \rho'_A \cdot s^{d+1}, \rho_B := \rho'_B \cdot s^{2(d+1)}$
3. For  $i \in [0..m]$ , define the polynomial  $P_i(X) := \rho'_A \cdot A_i(X) + \rho'_B X^{d+1} \cdot B_i(X) + \rho'_A \rho'_B X^{2(d+1)} \cdot C_i(X)$ . Define the  $\mathbb{F}_r$ -linear space  $V$  to be all polynomials  $f$  of degree at most  $3d + 3$  such that  $f \cdot P_i$  has a zero coefficient at  $X^{3d+3}$  for each  $i \in [0..m]$ .
4. Choose random  $f \in V$ , and let  $\beta := s^{q-(4d+3)} \cdot f(s)$ .
5. Let  $\gamma := \gamma' \cdot s^{q+2}$ .
6. output  $\text{params}^{\text{pin}}(s) := \text{params}_\phi(s, \rho_A, \rho_B, \alpha_A, \alpha_B, \alpha_C, \gamma, \beta)$ .

It can be verified that

1. When  $s$  is uniform in  $\mathbb{F}_r^*$ ,  $\text{params}^{\text{pin}}(s)$  is distributed as  $\text{params}_\phi(\text{secrets})$  for uniform value of secrets.
2.  $\text{params}^{\text{pin}}(s)$  can be efficiently computed from  $\text{challenge}_s$ .

The main point to see the second item is that the power  $s^{q+1}$  does not appear in any of the elements of  $\text{params}^{\text{pin}}(s)$  (this is immediate for most elements, and requires a calculation for elements containing  $\beta$ ).

Now  $B$  runs  $A$  on  $(\phi, x, \text{params}^{\text{pin}}(s))$  to obtain a purported proof  $\pi = (\pi_A, \pi_B, \pi_C, \pi'_A, \pi'_B, \pi'_C, \pi_K, \pi_H)$ .

$B$  also runs  $E_A, E_B, E_C$  on  $\text{params}^{\text{pin}}(s)$  to obtain polynomials  $A, B, C$  described above, and attempts to find a vector  $c$  of coefficients as above. Because of Item 1, together with the KOE assumption and the reasoning above, we know that with probability at least  $\eta - \text{negl}(\log r)$  over  $s$ ,

$$A_{i_0}(s)\rho_A \cdot g_1 + \pi_A = A(s)\rho_A \cdot g_1; \pi_B = B(s)\rho_B \cdot g_2; \pi_C = C(s)\rho_A\rho_B \cdot g_1,$$

but one of the following happened

1. There does not exist a vector  $c$  as described above.
2. Such  $c$  exists but is not a valid QAP witness for  $(\phi, x)$

Define the polynomial

$$R(X) := \rho'_A X^{d+1} \cdot A(X) + \rho'_B X^{2(d+1)} \cdot B(X) + \rho'_A \rho'_B X^{3(d+1)} \cdot C(X).$$

These two cases are equivalent, respectively, to the following two.

1.  $R(X)$  is not in the subspace  $V$ .
2.  $P(X) := A(X) \cdot B(X) - C(X)$  is not a multiple of  $Z(X)$ .

Suppose that  $R(X)$  is not in  $V$ . We show that in this case  $B$  can efficiently compute  $s^{q+1} \cdot g_1$ : It follows from Lemma 10 of [GGPR13] that except with probability  $1/r$  (over  $s$  and the inner randomness of  $\text{params}^{\text{pin}}$ ),  $R'(X) := X^{q-(4d+3)} \cdot f(X) \cdot R(X)$  has a non-zero coefficient at  $X^{q+1}$ . But note that as  $\pi$  was valid,

$$\pi_K = \beta \cdot (\rho_A \cdot A(s) + \rho_B \cdot B(s) + \rho_A \rho_B \cdot C(s)) \cdot g_1 = R'(s) \cdot g_1.$$

$B$  can thus use  $\text{challenge}$  to erase all elements of  $R'(s) \cdot g_1$  of powers different than  $q + 1$ , obtaining  $s^{q+1} \cdot g_1$ .

Now suppose that  $P(X)$  is not a multiple of  $Z(X)$ . The same argument as in [PHGR16] can now be used to obtain  $e(g_1, g_2)^{\frac{1}{s+t}}$ , for some  $t \in \mathbb{F}_r^*$ .  $\square$

We say an adversary  $A$  defeats the protocol, if it is able to produce a set of parameters for which it can construct a valid proof, when COMMIT is replaced by a random oracle. More formally,

**Definition 3.7.** *Let  $B$  be an adversary controlling  $n - 1$  out of  $n$  players in our protocol. We assume  $B$  is deterministic (as we can fix its' randomness to maximize its' success probability as defined next). Let  $P \in \{P_1, \dots, P_n\}$  be the player not controlled by  $B$ . We say  $B$   $\delta$ -defeats the protocol on  $(\phi, x)$  if with probability at least  $\delta$  over the randomness of  $P$  in the protocol, and over the choices of a random oracle choosing the output values of COMMIT in the protocol description, the protocol verifier accepts the transcript, and  $B$  afterwards produces a proof  $\pi$  such that  $V(\phi, x, \pi, \text{params}_\phi^B) = \text{acc}$ , where  $\text{params}_\phi^B$  are the Pinocchio parameters for instance  $\phi$  that were generated by the protocol.*

The correctness of the protocol lies in the following theorem.

**Theorem 3.8.** *For any efficient  $B$  controlling some subset of  $n - 1$  out of  $n$  players, there is an efficient  $A$  such that the following holds. Fix any instance  $\phi$  and input  $x$ . Suppose that  $B$   $\delta$ -defeats the protocol on  $(\phi, x)$ . Then  $A$   $\frac{\delta}{\text{poly}(\log r)}$ -defeats Pinocchio on  $(\phi, x)$ . In particular, if  $B$ 's success probability is non-negligible, so is  $A$ 's success probability.*

Before proving the theorem note that an immediate corollary of Theorems 3.6 and 3.8 is

**Corollary 3.9.** *[Knowledge Soundness of Protocol] For any efficient  $B$  controlling some subset of  $n - 1$  out of  $n$  players, there is an efficient extractor  $E$  such that the following holds. Fix any instance  $\phi$  and input  $x$ . Suppose that  $B$   $\delta$ -defeats the protocol on  $(\phi, x)$ . Then  $E$  produces a witness  $\omega$  satisfying  $(\phi, x)$  with probability  $\frac{\delta}{\text{poly}(\log r)}$  over  $\text{secrets} \in (\mathbb{F}_r^*)^8$ , when given  $(\phi, x, \text{params}_\phi(\text{secrets}))$  as input.*

We proceed to prove Theorem 3.8.

### Proof of Theorem 3.8

For ease of notation, we assume that  $B$  controls  $P_2, \dots, P_n$ . Also, we describe a non-uniform algorithm making choiced depending on  $(\phi, x)$ . However, inspection shows that making all these choices uniformly (and independently of  $(\phi, x)$ ) succeeds with probability  $\delta/\text{poly} \log r$ . We denote by  $\mathcal{R}$  the random oracle that chooses the values of COMMIT in the protocol. We assume the range (i.e. domain of replies) of  $\mathcal{R}$  is of size  $M = \text{poly}(r)$  which is exponential in our prespective. We will denote by  $\pi$  the purported proof and  $\text{params}_\phi^B$  the Pinocchio parameters generated in the protocol when  $B$  is participating. (These are randomized functions of various elements as will be discussed below). We will say  $\text{params}_\phi^B$  and  $\pi$  are *accepted by  $V$* , if  $V(\phi, x, \text{params}_\phi^B, \pi) = \text{acc}$ . It will be convenient to view the protocol as divided into two main phases.

1. The *commit and prove phase* which consists of Round 1 and Parts 1 – 3 of Round 2, i.e., all parts of Round 2 except the random powers subprotocol.
2. the *compute parameters phase* which consists of the random powers subprotocol in Round 2, together with Rounds 3 and 4.

Let  $\mathbf{e} = \{\mathbf{e}_i\}_{i \in [n]}$  be the set of elements broadcasted in Round 2 Part 1 during some execution of the protocol. Inspection of the protocol shows that



1. If all players follow the protocol, the transcript of the compute parameters phase is a deterministic function  $\text{comp-transcript}(e)$  of  $e$ .
2. Using the correctness of the  $\text{sameRatio}(\cdot)$  method, given the value of  $e$  in the commit and prove phase, if one of the players writes a message that does not coincide with  $\text{comp-transcript}(e)$  in the compute parameters phase, the transcript will be accepted by the protocol verifier with probability at most  $2/r$ . Thus, we assume that after the commit and prove phase,  $B$  follows the protocol correctly in the compute parameters phase; as otherwise we may replace him by another adversary  $B'$  that does so, and  $\delta - \text{negl}(\log r)$ -defeats the protocol.
3. In Round 2 Part 3, whenever  $B$  broadcasts an element  $R$  in one of the nizks, if he has not queried  $\mathcal{R}(R \circ h)$  where  $h$  will be the appropriate element  $h_{s,j}$ , the transcript will be accepted with probability at most  $1/M = \text{negl}(\log r)$ . Thus we can assume  $B$  always makes these queries, as otherwise he may be replaced with an  $B'$  that does and  $\delta - \text{negl}(\log r)$  defeats the protocol.
4. Similarly, if  $B$  has not queried  $\mathcal{R}(e_i)$  before broadcasting  $h_i$ , and has not indeed broadcasted  $\mathcal{R}(e_i)$  as  $h_i$ , where  $e_i$  is what he will broadcast in Round 2 Part 1 his success probability is negligible, and we can assume this is not the case.

Note that  $P_1$ , acting honestly makes 10 calls to  $\mathcal{R}$ - one in the first round to compute his message  $h_1$ , and 9 to compute the elements  $h, \{h_{i,s}\}$  in Round 2 Part 3. Let us assume  $B$  makes exactly  $Q'$  queries to  $\mathcal{R}$  during Round one and two, and let  $Q := Q' + 10$  be the total number of queries made to  $\mathcal{R}$ . Note that  $Q = \text{poly}(\log r)$  since the size of  $B$  is  $\text{poly}(\log r)$ . Denote the answers of  $\mathcal{R}$  by  $C := \{c_1, \dots, c_Q\}$ . Denote the queries by  $q_1, \dots, q_Q$ . Assume  $q_1, \dots, q_{Q/2}$  are exactly the ones made before the broadcast of  $e_1$  in Round 2. Denote by  $M$  the set of honest messages of  $P_1$  in the Round 2 part of the commit and prove phase, that are not values of  $\mathcal{R}$ - so  $M$  consists of the values  $e_i$  and  $R$ -values of the nizks from Round 2.

Under this assumption, together with items 2 and 3 above, the whole protocol transcript, and in particular the Pinocchio parameters  $\text{params}_\phi^B$  and the purported proof  $\pi$  generated by  $B$ , are a deterministic function  $F$  of  $(C, M)$ ; i.e., we can denote  $(\text{params}_\phi^B, \pi) = F(C, M)$ . From the fact that  $B$   $\delta$ -defeats the protocol, we know that there is a set of density  $\delta$  of sequences  $(C, M)$  that cause  $B$  to produce a valid proof  $\pi$  when  $V$  uses  $\text{params}_\phi^B$ . We can thus, using an averaging argument, fix a set of values  $S$  for  $(C, M)$  such that

1.  $S$  has probability mass  $\delta' = \delta - \text{negl}(\log r)$  in the space of all possible values for  $(C, M)$ , when  $C$  is random, and  $M$  is distributed according to an honest player  $P_1$ 's messages.
2.  $C$  contains all distinct elements.
3. For any  $(C, M) \in S$ ,  $F(C, M)$  is accepted by  $V$ .

Denote  $E := \cup_{i \in [2..n]} \text{secrets}_i$ , and enumerate the elements of  $E$  somehow as  $E_1, \dots, E_\ell$ , where  $\ell := 8 \cdot (n - 1)$ . Note that the elements of  $E$  are determined (although not efficiently) by the protocol transcript and thus by  $(C, M)$ . Note that in Round 2  $B$  has to present Schnorr nizk proofs for all elements of  $E$ , each requiring a query to  $\mathcal{R}$  on the corresponding element  $R \circ h$ . By another averaging argument similar to the “forking lemma”, there exists a permutation  $\sigma$  on  $[\ell]$  and indices  $1 \leq i_1 < \dots < i_\ell \leq Q$  such that there is a subset of  $T \subset S$  of density (meaning probability mass)  $\delta'' := \delta'/Q^\ell$  (in the space of all values for  $(C, M)$ ) such that for each  $(C, M) \in T$

1.  $F(C, M)$  is accepted by  $\mathbb{V}$ .
2. When executing the protocol with  $(C, M)$ , for each  $j \in [\ell]$ ,  $B$  uses the value  $c_{i_j}$  for the challenge  $c$  in the nizk of  $E_{\sigma(j)}$ .

We assume from now on that  $\sigma$  is the identity for simplicity of notation. Yet another averaging argument, using the non-negligibility of  $\delta''$ , allows us to construct a string  $C^*$  such that

1.  $(C^*, M) \in T$  with probability  $\delta''$  over  $M$ .
2. For any  $j \in [\ell]$ , there are strings  $(C', M'), (C'', M') \in T$ , i.e., that agree on the  $M'$  part, such that  $C'$  and  $C''$  agree with  $C^*$  on first  $i_j - 1$  indices, but disagree with each other on the  $i_j$ 'th coordinate.

We now note an important point:

Fix some  $j \in [\ell]$ . Then any string  $(C', M') \in T$  in which  $C'$  agrees with  $C^*$  on indices  $1, \dots, i_j - 1$ , must lead to the same value of  $E_j$ . This is because conditioned on being in  $T$ , the query  $q_{i_j}$  to  $\mathcal{R}$  will contain  $\text{rp}_{E_j}^1$  - which uniquely determines  $E_j$ , and the value of  $q_{i_j}$  is a deterministic function of  $c_1, \dots, c_{i_j-1}$ , when  $i_j \leq Q/2$ , and otherwise using item 4  $E_j$  is determined by  $c_1, \dots, c_{Q/2}$ . The second property above about the elements  $(C', M'), (C'', M') \in T$  implies we have access to two valid Schnorr nizks for  $E_j$  with the same  $R$  but different challenges  $c$ , which implies using the well-known Schnorr extractability property that  $A$  can extract the value  $E_j$  used by  $B$  given any  $(C^*, M) \in T$ .

Now let  $T'$  be the subset of  $T$  consisting of elements beginning with  $C^*$

Now let  $\text{params}_\phi = \text{params}_\phi(\text{secrets})$  be the parameters given as a challenge to  $A$  (for which he should construct an accepting proof). Let  $\text{secrets}_1 := \text{secrets}/(\text{secrets}_2 \cdots \text{secrets}_n)$  be the coordinate wise division of the corresponding secrets vectors. Recall  $E = \text{secrets}_2 \cup \dots \cup \text{secrets}_n$  is fixed conditioned on  $(C, M) \in T'$ , and  $A$  has extracted the values  $E$ . Inspection of the protocol shows that  $A$  can efficiently play the role of  $P_1$  when he chooses this value of  $\text{secrets}_1$ , just from knowing  $E$  and  $\text{params}_\phi(\text{secrets})$ , *with one potential exception*: Constructing valid nizks of the elements of  $\text{secrets}_1$  *which he does not know*. However, he can do this also using his ability to program  $\mathcal{R}$ . He will choose random  $\mathbb{F}_r$  elements as the answers  $u$  in the nizks and then compute  $R := c \cdot H - u \cdot f$ . and set  $\mathcal{R}(R) = c$ , unless  $\mathcal{R}(R)$  has been queried by  $B$  in which case he aborts. He then conducts the protocol with  $B$  using the values  $(C^*, M)$ , and outputs the proof  $\pi$  generated by  $B$ . Note that when following this strategy  $\text{secrets}_1$  and all the corresponding  $R$ 's in the nizks are uniformly distributed. Thus the probability that  $(C^*, M) \in T'$  when  $M$  is derived from the  $R$ 's and  $\text{secrets}_1$  is at least  $\delta''$ . Thus the probability that  $F(C^*, M)$  will satisfy  $\mathbb{V}$  when using this strategy is at least  $\delta''$  which is non-negligible when  $\delta$  is non-negligible.  $\square$

## Acknowledgements

We thank Eli Ben-Sasson, Alessandro Chiesa, Jens Groth, Daira Hopwood, Hovav Shacham, Madars Virza, Nathan Wilcox and Zooko Wilcox for helpful discussions. We thank Daira Hopwood for pointing out some technical inaccuracies.

## References

- [BCG<sup>+</sup>15] E. Ben-Sasson, A. Chiesa, M. Green, E. Tromer, and M. Virza. Secure sampling of public parameters for succinct zero knowledge proofs. In *2015 IEEE Symposium on Security and Privacy, SP 2015, San Jose, CA, USA, May 17-21, 2015*, pages 287–304, 2015.
- [BCPR14] N. Bitansky, R. Canetti, O. Paneth, and A. Rosen. On the existence of extractable one-way functions. In *Symposium on Theory of Computing, STOC 2014, New York, NY, USA, May 31 - June 03, 2014*, pages 505–514, 2014.
- [BCTV14] E. Ben-Sasson, A. Chiesa, E. Tromer, and M. Virza. Succinct non-interactive zero knowledge for a von neumann architecture. In *Proceedings of the 23rd USENIX Security Symposium, San Diego, CA, USA, August 20-22, 2014.*, pages 781–796, 2014.
- [CFH<sup>+</sup>15] C. Costello, C. Fournet, J. Howell, M. Kohlweiss, B. Kreuter, M. Naehrig, B. Parno, and S. Zahur. Geppetto: Versatile verifiable computation. In *2015 IEEE Symposium on Security and Privacy, SP 2015, San Jose, CA, USA, May 17-21, 2015*, pages 253–270, 2015.
- [GGPR13] R. Gennaro, C. Gentry, B. Parno, and M. Raykova. Quadratic span programs and succinct nizks without pcps. In *Advances in Cryptology - EUROCRYPT 2013, 32nd Annual International Conference on the Theory and Applications of Cryptographic Techniques, Athens, Greece, May 26-30, 2013. Proceedings*, pages 626–645, 2013.
- [PHGR16] B. Parno, J. Howell, C. Gentry, and M. Raykova. Pinocchio: nearly practical verifiable computation. *Commun. ACM*, 59(2):103–112, 2016.
- [Sch89] C. Schnorr. Efficient identification and signatures for smart cards. In *Advances in Cryptology - CRYPTO '89, 9th Annual International Cryptology Conference, Santa Barbara, California, USA, August 20-24, 1989, Proceedings*, pages 239–252, 1989.

## A Actual, more complicated version of $e_i$ in code

For each  $i \in [n]$ ,  $P_i$  first constructs  $\text{elements}_i$  as in Subsection 2.1. That is

1. As described in Generate a set of uniform elements in  $\mathbb{F}_r^*$

$$\text{secrets}_i := \{\tau_i, \rho_{A,i}, \rho_{B,i}, \alpha_{A,i}, \alpha_{B,i}, \alpha_{C,i}, \beta_i, \gamma_i\}$$

, and let

$$\begin{aligned} \text{elements}_i := \{ & \tau_i, \rho_{A,i}, \rho_{B,i}, \alpha_{A,i}, \alpha_{B,i}, \alpha_{C,i}, \beta_i, \gamma_i, \rho_{A,i}\alpha_{A,i}, \rho_{B,i}\alpha_{B,i}, \\ & \rho_{A,i}\rho_{B,i}, \rho_{A,i}\rho_{B,i}\alpha_{C,i}, \beta_i\gamma_i \} \end{aligned}$$

2. Now each player generates a somewhat complex set of group elements from its set of secrets. We omit the index  $i$  for clarity of notation, but it should be appended to all elements below:
  - (a)  $P_i$  chooses random elements  $f_1, f_2, f_3 \in \mathbb{G}_2 \setminus \{0\}$  and random elements  $f_4, f_5, f_6, f_7, f_8 \in \mathbb{G}_1 \setminus \{0\}$ .

(b)  $P_i$  stores the sets of  $\mathbb{G}_2$  elements

$$\begin{aligned} \mathbf{e}_i^2 := \{ & f_1, f_1 \cdot \rho_A, f_1 \cdot \rho_A \alpha_A, f_1 \cdot \rho_A \rho_B \alpha_C, f_1 \cdot \rho_A \rho_B, f_1 \cdot \rho_A \rho_B \alpha_B, \\ & f_2, f_2 \cdot \beta, f_2 \cdot \beta \gamma, f_3, f_3 \cdot \tau \}, \end{aligned}$$

and the set of  $\mathbb{G}_1$  elements

$$\mathbf{e}_i^1 := \{ f_4, f_4 \cdot \alpha_A, f_5, f_5 \cdot \alpha_C, f_6, f_6 \cdot \rho_B, f_7, f_7 \cdot \rho_A, f_8, f_8 \cdot \gamma \}.$$

3. Finally, define  $\mathbf{e}_i := \mathbf{e}_i^1 \circ \mathbf{e}_i^2$ .

**Validity of more complicated definition** The only requirement for  $\mathbf{e}_i$  to run the protocol is that we always have the needed  $s$ -pair for each  $s \in \text{elements}_i$ . Inspection shows this is the case with the definition here. For example  $P_i$  has broadcasted (omitting index  $i$ )  $f_1, f_1 \rho_A$  and  $f_1 \rho_A \rho_B$  as part of  $\mathbf{e}_i^2$ , out of which we can construct the  $\rho_A$ -pair  $(f_1, f_1 \rho_A)$ , the  $\rho_B$ -pair  $(f_1 \rho_A, f_1 \rho_A \rho_B)$ , and the  $\rho_A \rho_B$ -pair  $(f_1, f_1 \rho_A \rho_B)$ . Since here we don't have a  $\mathbb{G}_1$ - $s$ -pair and  $\mathbb{G}_2$ - $s$ -pair for each  $s \in \text{elements}_i$ , less consistency checks are performed in Part 2 of Round 2. (Note that to run the protocol we don't need an  $s$ -pair for each  $s \in \text{elements}_i$  in each group. For example, we only need a  $\mathbb{G}_2$ - $\rho_A$ -pair which is used in Round 3 to compute  $PK_A$ , but we never use a  $\mathbb{G}_1$ - $\rho_A$ -pair).

## B Implementation details

In our implementation we use the libsnark `alt_bn128` curve implementation where

1.  $\mathbb{G}_1 = E/\mathbb{F}_q$  is a BN curve over  $\mathbb{F}_q$ . That is the set of solutions in  $\mathbb{F}_q^2$  of an equation of the form  $y^2 = x^3 + b$ .
2.  $\mathbb{G}_2 = E'/\mathbb{F}_{q^2}$  is a subgroup of order  $r$  of a sextic twist of  $\mathbb{G}_1$ . Where a sextic twist of  $\mathbb{G}_1$  means the set of solutions in  $\mathbb{F}_{q^2}$  of  $y^2 = x^3 + b/\xi$ , where  $\xi \in \mathbb{F}_{q^2} \setminus \mathbb{F}_q$  is an element such that the polynomial  $W^6 - \xi$  is irreducible over  $\mathbb{F}_{q^2}$ .
3.  $\mathbb{G}_t$  is a subgroup of order  $r$  in  $\mathbb{F}_{q^{12}}$ .